



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **11044133 A**(43) Date of publication of application: **16.02.99**

(51) Int. Cl. **E05B 19/10**
E05B 19/04
G04B 47/04

(21) Application number: **09358694**(71) Applicant: **SHINANONO KUNIYA:KK**(22) Date of filing: **26.12.97**(72) Inventor: **MASUZAWA KAZUYUKI**(30) Priority: **28.05.97 JP 09138607**(54) **INSTALLING COVER FOR KEY**

COPYRIGHT: (C)1999,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To easily perform key operation by installing it on a key merely formed of a metallic plate, and carry it without exposing the key by installing a lug part inserted into an inserting hole on a cover main body so as to be mountable/dismountable in a key installing cover installed in a metallic lug part of the key.

SOLUTION: In a cover main body 31 formed out of resin or the like in almost the same size as a lug part of a key, its thickness is made larger than the thickness of the key 32, and an inserting hole 44 to insert the lug part 32b by narrowly working the lug part of the key 32, is formed in its one wall surface. A screw hole 49 reaching the inserting hole 44 is also vertically formed to the inserting hole 44, and a screw 50 is screw-fitted to this screw hole 49. When a tip part of the screw 50 enters a fitting hole formed in the key 32, the key 32 is fixed to the cover main body 31. The fixed key 32 can also be easily separated from the cover main body 31 by removing the screw 50.

